

View Online at <https://aerobasegroup.com/nsn/5962-01-341-3385>

**Overall Height:**

Between 0.270 inches and 0.330 inches

**Body Length:**

Between 1.540 inches and 1.594 inches

**Body Width:**

Between 1.540 inches and 1.594 inches

**Body Height:**

Between 0.100 inches and 0.140 inches

**Maximum Power Dissipation Rating:**

550.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and burn in and bipolar and w/enable

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Pin grid array

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

Over 95 input

**Design Function And Quantity:**

1 gate, array

**Current Rating Per Characteristic:**

10.00 milliamperes average forward current averaged over a full 60-hz cycle absolute

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

-300.0 millivolts power source and 7.0 volts power source

**Capitance Rating Per Characteristic:**

Between err-060 and err-060

**Time Rating Per Characteristic:**

75.00 nanoseconds propagation delay

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

180 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0