NSN 5962-01-341-5879

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-341-5879

| Overa | II I | end | ath. |
|----------|------|------|------|
| O v Cı a | | .611 | uui. |

Between 1.640 inches and 1.870 inches

Overall Width:

Between 1.640 inches and 1.870 inches

Body Length:

Between 0.935 inches and 0.970 inches

Body Width:

Between 0.935 inches and 0.970 inches

Body Height:

Between 0.090 inches and 0.145 inches

Maximum Power Dissipation Rating:

1.5 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Bidirectional and burn in and electrostatic sensitive and medium voltage and programmed and ultraviolet erasable

Inclosure Material:

Ceramic

Inclosure Configuration:

Beam chip

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

64 input

Current Rating Per Characteristic:

300.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, programme (ewego disk-6)

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Chacteristic:

90.00 nanoseconds access

Memory Device Type:

Programmed

Precious Material And Location:

Terminals gold

Precious Material:

Gold

NSN 5962-01-341-5879

Memory Microcircuit - Page 2 of 2



| Terminal Type A | nd Quantity: |
|-----------------|--------------|
|-----------------|--------------|

68 beam lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0