

View Online at <https://aerobasegroup.com/nsn/5962-01-341-5884>

**Body Length:**

1.060 inches

**Body Width:**

0.310 inches

**Body Height:**

0.200 inches

**Maximum Power Dissipation Rating:**

320.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Ultraviolet erasable and burn in and asynchronous and hermetically sealed and programmed

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

10 input

**Current Rating Per Characteristic:**

25.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable

**Terminal Surface Treatment:**

Solder

**Product Name:**

Tre rotating priorities, odd bank

**Voltage Rating And Type Per Characteristic:**

7.0 volts power source

**Capitance Rating Per Characteristic:**

12.00 input picofarads

**Time Rating Per Characteristic:**

50.00 nanoseconds input to output access

**Memory Device Type:**

Pal

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

20 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0