## NSN 5962-01-341-7083

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-341-7083

Overa	II I	end	ath.
O v Cı a		.611	uui.

Between 1.640 inches and 1.870 inches

**Overall Width:** 

Between 1.640 inches and 1.870 inches

**Body Length:** 

Between 0.935 inches and 0.970 inches

**Body Width:** 

Between 0.935 inches and 0.970 inches

**Body Height:** 

Between 0.090 inches and 0.145 inches

**Maximum Power Dissipation Rating:** 

1.5 watts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Storage Tempurature Range:** 

-65.0/+150.0 degrees celsius

**Features Provided:** 

Bidirectional and burn in and electrostatic sensitive and medium voltage and programmed and ultraviolet erasable

**Inclosure Material:** 

Ceramic

**Inclosure Configuration:** 

Beam chip

**Output Logic Form:** 

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:** 

64 input

**Current Rating Per Characteristic:** 

300.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:** 

Solder

**Product Name:** 

Microcircuit, programme (ewego disk-7)

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Chacteristic:

90.00 nanoseconds access

**Memory Device Type:** 

Programmed

**Precious Material And Location:** 

Terminals gold

**Precious Material:** 

Gold

## NSN 5962-01-341-7083

Memory Microcircuit - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

68 beam lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0