## NSN 5962-01-341-7411

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-341-7411

Overall Height:
0.425 inches
Overall Width:
Between 0.590 inches and 0.630 inches
Body Length:
2.096 inches
Body Width:
Between 0.510 inches and 0.620 inches
Body Height:
0.210 inches
Maximum Power Dissipation Rating:
794.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Bipolar and burn in and programmed and monolithic and schottky and 3-state output
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
12 input
Case Outline Source And Designator:
D-6 mil-m-38510
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, digital, bipolar, programmable read only memory, 1k x 4
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
85.00 nanoseconds access
Memory Device Type:
Prom
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:

18 printed circuit

## NSN 5962-01-341-7411

Memory Microcircuit - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0