NSN 5962-01-341-7950

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-341-7950

View Offilite at https://defobasegroup.com/nsi//0302-01-041-7330
Overall Length:
Between 0.665 inches and 0.935 inches
Body Length:
Between 0.165 inches and 0.185 inches
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Overall Diameter:
Between 0.335 inches and 0.370 inches
Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and w/current limiter and positive outputs
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
5 input
Design Function And Quantity:
1 regulator, voltage
Case Outline Source And Designator:
A-1 mil-m-38510
Current Rating Per Characteristic:
10.50 milliamperes peak forward surge current not applicable
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
50.0 volts input
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:

Yes - demil/mli

NSN 5962-01-341-7950

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0