## NSN 5962-01-341-7955

Memory Microcircuit - Page 1 of 2

**Overall Length:** 

6.0 grams



View Online at https://aerobasegroup.com/nsn/5962-01-341-7955

1.111 inches			
Overall Height:			
0.425 inches			
Body Length:			
1.111 inches			
Body Width:			
Between 0.350 inches and 0.410 inches			
Body Height:			
Between 0.155 inches and 0.210 inches			
Maximum Power Dissipation Rating:			
495.0 milliwatts			
Operating Tempurature Range:			
-55.0/+125.0 degrees celsius			
Storage Tempurature Range:			
-65.0/+150.0 degrees celsius			
Features Provided:			
Hermetically sealed and burn in and static operation and monolithic			
Inclosure Material:			
Ceramic			
Inclosure Configuration:			
Dual-in-line			
Output Logic Form:			
Complementary-metal oxide-semiconductor logic			
Input Circuit Pattern:			
16 input			
Case Outline Source And Designator:			
D-7 mil-m-38510			
Current Rating Per Characteristic:			
90.00 milliamperes reverse current, dc absolute			
Terminal Surface Treatment:			
Solder			
Voltage Rating And Type Per Characteristic:			
-0.5 volts power source and 7.0 volts power source			
Capitance Rating Per Characteristic:			
Err-060 and err-060			
Time Rating Per Chacteristic:			
25.00 nanoseconds access			
Memory Device Type:			
Ram			
Unpackaged Unit Weight:			

## NSN 5962-01-341-7955

Memory Microcircuit - Page 2 of 2



Test	Data	Docum	ent
------	------	-------	-----

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

22 printed circuit

•

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0