# NSN 5962-01-341-7955

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-341-7955

**Overall Length:** 1.111 inches **Overall Height:** 0.425 inches **Body Length:** 1.111 inches **Body Width:** Between 0.350 inches and 0.410 inches **Body Height:** Between 0.155 inches and 0.210 inches **Maximum Power Dissipation Rating:** 495.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and static operation and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input **Case Outline Source And Designator:** D-7 mil-m-38510 **Current Rating Per Characteristic:** 90.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source **Capitance Rating Per Characteristic:** Err-060 and err-060 **Time Rating Per Chacteristic:** 25.00 nanoseconds access Memory Device Type: Ram **Unpackaged Unit Weight:** 

6.0 grams

## NSN 5962-01-341-7955

Memory Microcircuit - Page 2 of 2



#### Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

22 printed circuit

Shelf Life:

N/a

## Unit Of Measure:

---

### Demilitarization:

Yes - demil/mli

Fiig:

A458a0