## NSN 5962-01-341-7956

Memory Microcircuit - Page 1 of 2

Overall Length: 1.060 inches Overall Height:



View Online at https://aerobasegroup.com/nsn/5962-01-341-7956

0.400 inches
Body Length:
1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.130 inches and 0.185 inches
Maximum Power Dissipation Rating:
320.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and ultraviolet erasable and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
18 input
Case Outline Source And Designator:
D-8 mil-m-38510
Current Rating Per Characteristic:
40.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
300 gate erasable programmable logic device
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:
12.00 input pascal dense structural 65 and 12.00 output pascal dense structural 65
Time Rating Per Chacteristic:
50.00 nanoseconds access
Memory Device Type:
Programmable

## NSN 5962-01-341-7956

Memory Microcircuit - Page 2 of 2

**Fiig:** A458a0



Unpackaged Unit Weight:
2.4 grams
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)
Terminal Type And Quantity:
20 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli