NSN 5962-01-342-0782

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-342-0782

Overall Length:
0.880 inches
Overall Height:
0.400 inches
Overall Width:
0.505 inches
Body Length:
0.880 inches
Body Width:
0.505 inches
Body Height:
0.200 inches
Maximum Power Dissipation Rating:
75.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and electrostatic sensitive and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
3 input
Design Function And Quantity:
4 annillator, alask and 4 annillator, ametal controllad

1 oscillator, clock and 1 oscillator, crystal controlled

Current Rating Per Characteristic:

15.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Swept quartz crystal controlled clock oscillator

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Hybrid Technology Type:

Monolithic

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-342-0782

Hybrid Microcircuit - Page 2 of 2



Ferminal	Type	And	Quantity:
-----------------	------	-----	-----------

1 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0