## NSN 5962-01-342-3950

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-342-3950

**Overall Length:** 

Between 0.342 inches and 0.358 inches

**Overall Height:** 

Between 0.060 inches and 0.100 inches

**Overall Width:** 

Between 0.342 inches and 0.358 inches

**Body Length:** 

Between 0.342 inches and 0.358 inches

**Body Width:** 

Between 0.342 inches and 0.358 inches

**Body Height:** 

Between 0.060 inches and 0.100 inches

**Maximum Power Dissipation Rating:** 

30.0 milliwatts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Storage Tempurature Range:** 

-65.0/+150.0 degrees celsius

**Features Provided:** 

Monolithic and w/reset and w/resistor

**Inclosure Material:** 

Ceramic

**Inclosure Configuration:** 

Leadless flat pack

**Input Circuit Pattern:** 

3 input

**Design Function And Quantity:** 

1 power supply

**Case Outline Source And Designator:** 

C-2 mil-m-38510

**Current Rating Per Characteristic:** 

3.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:** 

Solder

**Product Name:** 

Supply voltage supervisors

**Voltage Rating And Type Per Characteristic:** 

20.0 volts power source

**Test Data Document:** 

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

20 leadless

## NSN 5962-01-342-3950

Linear Microcircuit - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A458a0