NSN 5962-01-342-3950

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-342-3950

Overall Length:

Between 0.342 inches and 0.358 inches

Overall Height:

Between 0.060 inches and 0.100 inches

Overall Width:

Between 0.342 inches and 0.358 inches

Body Length:

Between 0.342 inches and 0.358 inches

Body Width:

Between 0.342 inches and 0.358 inches

Body Height:

Between 0.060 inches and 0.100 inches

Maximum Power Dissipation Rating:

30.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and w/reset and w/resistor

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Input Circuit Pattern:

3 input

Design Function And Quantity:

1 power supply

Case Outline Source And Designator:

C-2 mil-m-38510

Current Rating Per Characteristic:

3.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Supply voltage supervisors

Voltage Rating And Type Per Characteristic:

20.0 volts power source

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 leadless

NSN 5962-01-342-3950

Linear Microcircuit - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0