NSN 5962-01-342-3952

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-342-3952

View Online at https://aerobasegroup.com/nsn/5962-01-342-3952
Overall Length:
0.840 inches
Overall Height:
0.400 inches
Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Radar set an/apq-150
Features Provided:
Hermetically sealed and burn in and fast carry and monolithic and electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
9 input
Design Function And Quantity:
1 adder, full, binary
Case Outline Source And Designator:
D-2 mil-m-38510
Current Rating Per Characteristic:
160.00 microamperes supply
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 6.0 volts power source
Time Rating Per Chacteristic:
18.20 nanoseconds propagation delay
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards individual manu

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-342-3952

Digital Microcircuit - Page 2 of 2



Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0