
## NSN 5962-01-343-0671

Digital Microcircuit - Page 1 of 2

**Overall Length:** 





## 0.870 inches **Overall Height:** 0.275 inches **Overall Width:** Between 0.300 inches and 0.320 inches **Body Length:** 0.870 inches **Body Width:** Between 0.245 inches and 0.255 inches **Body Height:** Between 0.125 inches and 0.135 inches **Operating Tempurature Range:** -40.0/+85.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** W/clock and w/reset and monolithic **Inclosure Material:** Ceramic Inclosure Configuration: Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 1 counter **Current Rating Per Characteristic:** 3.60 milliamperes reverse current, dc **Terminal Surface Treatment:** Solder **Product Name:** 4 decade counter with multiplexed 7-segment output drivers Voltage Rating And Type Per Characteristic: 6.5 volts power source **Capitance Rating Per Characteristic:** Err-060 **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a

## NSN 5962-01-343-0671

Digital Microcircuit - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

