

View Online at <https://aerobasegroup.com/nsn/5962-01-343-2490>

Overall Length:

1.060 inches

Overall Height:

0.400 inches

Body Length:

1.060 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.130 inches and 0.185 inches

Maximum Power Dissipation Rating:

300.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

High speed and 3-state output and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

8 buffer, inverting and 8 buffer, tri-state

Case Outline Source And Designator:

D-8 mil-m-38510

Current Rating Per Characteristic:

20.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

Err-060 and err-060

Time Rating Per Characteristic:

29.00 nanoseconds propagation delay time, high to low level output and 29.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

Terminal Type And Quantity:

20 printed circuit

Specification Data:

81349-mil-m-38510/657 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0