# NSN 5962-01-344-0180

Digital Microcircuit - Page 1 of 2



zigital microsiloan i ago i ol z
View Online at https://aerobasegroup.com/nsn/5962-01-344-0180
Overall Length:
0.785 inches
Overall Height:
0.400 inches
Body Length:
0.785 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
Hex 1 input
Design Function And Quantity:
6 schmitt trigger
Case Outline Source And Designator:
D-1 mil-m-38510
Current Rating Per Characteristic:
400.00 (11)

100.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:** 

Solder

**Voltage Rating And Type Per Characteristic:** 

-0.5 volts power source and 6.0 volts power source

**Capitance Rating Per Characteristic:** 

10.00 input pascal dense structural 65 and 15.00 output pascal dense structural 65

**Time Rating Per Chacteristic:** 

16.00 nanoseconds propagation delay

**Unpackaged Unit Weight:** 

2.0 grams

# NSN 5962-01-344-0180

Digital Microcircuit - Page 2 of 2



#### **Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

14 printed circuit

### **Specification Data:**

81349-mil-m-38510/757 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

#### Demilitarization:

Yes - demil/mli

Fiig:

A458a0