

View Online at <https://aerobasegroup.com/nsn/5962-01-344-0903>

Overall Length:

Between 0.342 inches and 0.358 inches

Overall Height:

Between 0.060 inches and 0.100 inches

Overall Width:

Between 0.342 inches and 0.358 inches

Body Length:

Between 0.342 inches and 0.358 inches

Body Width:

Between 0.342 inches and 0.358 inches

Body Height:

Between 0.060 inches and 0.100 inches

Maximum Power Dissipation Rating:

297.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Bipolar and low power and schottky and monolithic and 3-state output

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

8 gate, buffer

Case Outline Source And Designator:

C-2 mil-m-38510

Current Rating Per Characteristic:

54.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Noninverting octal buffer gate (complementary control inputs)

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

23.00 nanoseconds propagation delay time, high to low level output and 23.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 leadless

Specification Data:

81349-mil-m-38510/324 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0