

View Online at <https://aerobasegroup.com/nsn/5962-01-344-4713>

**Overall Width:**

Between 0.735 inches and 1.000 inches

**Body Length:**

0.390 inches

**Body Width:**

Between 0.235 inches and 0.260 inches

**Body Height:**

Between 0.045 inches and 0.085 inches

**Maximum Power Dissipation Rating:**

22.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Bipolar and burn in and monolithic and schottky

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Compatible-current-sinking logic

**Input Circuit Pattern:**

8 input

**Design Function And Quantity:**

1 gate, nand

**Case Outline Source And Designator:**

F-2 mil-m-38510

**Current Rating Per Characteristic:**

40.00 milliamperes peak forward surge current megawatts

**Terminal Surface Treatment:**

Solder

**Product Name:**

8-input positive-nand gate

**Voltage Rating And Type Per Characteristic:**

5.0 volts power source

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0