NSN 5962-01-344-4714

Digital Microcircuit - Page 1 of 2

Overall Length: 1.060 inches Overall Height:

output



View Online at https://aerobasegroup.com/nsn/5962-01-344-4714

0.400 inches
Body Length:
1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.130 inches and 0.185 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
3-state output and monolithic and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
10 input
Design Function And Quantity:
8 transceiver
Case Outline Source And Designator:
D-8 mil-m-38510
Current Rating Per Characteristic:
100.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable
Terminal Surface Treatment:
Solder
Product Name:
Octal bidirectional transceiver
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:
15.00 input pascal dense structural 65 and 15.00 output pascal dense structural 65
Time Rating Per Chacteristic:
11.50 nanoseconds propagation delay time, high to low level output and 11.50 nanoseconds propagation delay time, low to high level

NSN 5962-01-344-4714

Digital Microcircuit - Page 2 of 2



Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 printed circuit

Specification Data:

81349-mil-m-38510/755 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0