NSN 5962-01-344-4998

Memory Microcircuit - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5962-01-344-4998

| 1.490 inches |
|---|
| Overall Height: |
| 0.432 inches |
| Body Length: |
| 1.490 inches |
| Body Width: |
| Between 0.500 inches and 0.610 inches |
| Body Height: |
| Between 0.172 inches and 0.217 inches |
| Maximum Power Dissipation Rating: |
| 1.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| W/disable and w/inhibit and w/enable and monolithic and ultraviolet erasable and programmable |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 17 input |
| Case Outline Source And Designator: |
| D-10 mil-m-38510 |
| Current Rating Per Characteristic: |
| 125.00 milliamperes reverse current, dc absolute |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -0.6 volts power source and 6.25 volts power source |
| Capitance Rating Per Characteristic: |
| Err-060 and err-060 |
| Time Rating Per Chacteristic: |
| 200.00 nanoseconds access |
| Memory Device Type: |
| Eeprom |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.) |
| |
| |

NSN 5962-01-344-4998

Memory Microcircuit - Page 2 of 2



| Ī | erminal | Type | And | Quant | tity: |
|---|---------|------|-----|-------|-------|
| | | | | | |

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0