NSN 5962-01-344-6183

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-344-6183

Overall Length:
1.280 inches
Overall Height:
0.400 inches
Body Length:
1.280 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Radar set an/apq-17 (v)
Features Provided:
Programmable and programmed and w/clock and hermetically sealed and burn in
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
16 input
Case Outline Source And Designator:
D-9 mil-m-38510
Current Rating Per Characteristic:
210.00 milliamperes supply
Terminal Surface Treatment:
Solder
Product Name:
Pal, 20r6, programmed
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
30.00 nanoseconds propagation delay
Memory Device Type:
Programmed
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)

NSN 5962-01-344-6183

Memory Microcircuit - Page 2 of 2



T	erm	inal	Type	Δnd	Ou	antity	,.
ı	GIIII	ıııaı	IVDE	Allu	чu	annını	

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0