NSN 5962-01-344-9322

Memory Microcircuit - Page 1 of 2

Overall Length: 1.290 inches Body Length: 1.290 inches



View Online at https://aerobasegroup.com/nsn/5962-01-344-9322

Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
Between 0.160 inches and 0.220 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
Storage Tempurature Range:
-55.0/+125.0 degrees celsius
End Application:
5895-01-167-7655 receiving set
Features Provided:
Hermetically sealed and burn in and electrostatic sensitive and ultraviolet erasable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
N-type metal oxide-semiconductor logic
Input Circuit Pattern:
13 input
Current Rating Per Characteristic:
115.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.3 volts power source and 6.0 volts power source
Capitance Rating Per Characteristic:
6.00 input pascal dense structural 65 and 12.00 output pascal dense structural 65
Time Rating Per Chacteristic:
450.00 nanoseconds delay
Memory Device Type:
Eprom
Unpackaged Unit Weight:
6.5 grams
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-344-9322

Memory Microcircuit - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0