

View Online at https://aerobasegroup.com/nsn/5962-01-345-0232

NSN 5962-01-345-0232 Digital Microcircuit - Page 1 of 2 **Overall Height:** 0.425 inches **Overall Width:** Between 0.590 inches and 0.630 inches **Body Length:** 2.096 inches **Body Width:** Between 0.510 inches and 0.620 inches **Body Height:** 0.210 inches **Maximum Power Dissipation Rating:** 1.03 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Asynchronous and burn in and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 22 input **Design Function And Quantity:** 1 transceiver **Case Outline Source And Designator:** D-5 mil-m-38510 **Terminal Surface Treatment:** Solder **Product Name:** Microcircuit, digital, cmos, universal asynchronous receiver transmitter Voltage Rating And Type Per Characteristic: 8.0 volts power source **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

40 printed circuit

Shelf Life:

N/a

NSN 5962-01-345-0232

Digital Microcircuit - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

