NSN 5962-01-345-1521

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-345-1521

Overall Length:

Between 1.308 inches and 1.332 inches

Overall Height:

0.280 inches

Overall Width:

Between 1.308 inches and 1.332 inches

Body Length:

Between 1.308 inches and 1.332 inches

Body Width:

Between 1.308 inches and 1.332 inches

Body Height:

Between 0.080 inches and 0.100 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

1260-01-165-3959 control-display sys

Features Provided:

Electrostatic sensitive and monolithic and 3-state output and bidirectional and burn in

Inclosure Material:

Ceramic

Inclosure Configuration:

Pin grid array

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

15 input and 50 input

Design Function And Quantity:

1 control

Current Rating Per Characteristic:

100.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Bus input/output controller, asic, standard cell, bus controller functional

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

Err-060 and err-060

NSN 5962-01-345-1521

Digital Microcircuit - Page 2 of 2



Test	Data	Docu	ıment
------	------	------	-------

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

120 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0