NSN 5962-01-345-1523

Hybrid Microcircuit - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5962-01-345-1523

2.100 inches				
Overall Height:				
0.500 inches				
Overall Width:				
1.870 inches				
Body Length:				
2.100 inches				
Body Width:				
1.870 inches				
Body Height:				
0.250 inches				
Maximum Power Dissipation Rating:				
810.0 milliwatts				
Operating Tempurature Range:				
-55.0/+125.0 degrees celsius				
Storage Tempurature Range:				
-65.0/+150.0 degrees celsius				
Features Provided:				
Hermetically sealed and burn in and hybrid and w/clock				
Inclosure Material:				
Ceramic				
Inclosure Configuration:				
Quad-in-line				
Output Logic Form:				
Transistor-transistor logic				
Input Circuit Pattern:				
49 input				
Design Function And Quantity:				
1 transceiver				
Current Rating Per Characteristic:				
170.00 milliamperes reverse current, dc absolute				
Terminal Surface Treatment:				
Solder				
Product Name:				
Mil-std-1553, bc/rtu/mt, transceiver multiplexed terminal				
Voltage Rating And Type Per Characteristic:				
-0.5 volts power source and 7.0 volts power source				
Time Rating Per Chacteristic:				
150.00 nanoseconds delay				
Hybrid Technology Type:				
Monolithic				

NSN 5962-01-345-1523

Hybrid Microcircuit - Page 2 of 2



Test	Data	Docu	ıment
------	------	------	-------

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

78 printed circuit

ro printoa onoa

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

Mil-std (military Standard):

Mil-std-1553 spec.