## NSN 5962-01-345-2673

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-345-2673

Overall Length:
0.405 inches
Overall Height:
0.400 inches
Body Length:
0.405 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and high speed and high precision
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
3 input
Design Function And Quantity:
1 comparator
Case Outline Source And Designator:
D-4 mil-m-38510
Current Rating Per Characteristic:
15.00 milliamperes supply
Terminal Surface Treatment:
Solder
Product Name:
Precision comparator
Voltage Rating And Type Per Characteristic:
-18.0 volts power source and 6.0 volts power source
Time Rating Per Chacteristic:
65.00 nanoseconds propagation delay
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:

8 printed circuit

## NSN 5962-01-345-2673

Linear Microcircuit - Page 2 of 2



	<b>L</b> -	11		ife	_
3	ne	п	_	пe	Ξ

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0