# NSN 5962-01-345-2677

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-345-2677

### **Body Length:**

Between 1.080 inches and 1.135 inches

#### **Body Width:**

Between 1.080 inches and 1.135 inches

#### **Body Height:**

Between 0.070 inches and 0.140 inches

## **Maximum Power Dissipation Rating:**

1.0 watts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### Features Provided:

Burn in and bidirectional and monolithic and w/common clock

#### Inclosure Material:

Ceramic

#### Inclosure Configuration:

Pin grid array

#### **Output Logic Form:**

Complementary-metal oxide-semiconductor logic

#### Input Circuit Pattern:

45 input

#### **Design Function And Quantity:**

1 processor, pulse

#### Case Outline Source And Designator:

P-bc mil-m-38510

#### **Current Rating Per Characteristic:**

300.00 microamperes average forward current averaged over a full 60-hz cycle not applicable

#### **Terminal Surface Treatment:**

Solder

#### **Product Name:**

Microcircuit, digital, cmos, signal processor

#### Voltage Rating And Type Per Characteristic:

-0.3 volts power source and 7.0 volts power source

#### Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

### **Terminal Type And Quantity:**

68 pin

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5962-01-345-2677

Digital Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

