NSN 5962-01-345-2677

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-345-2677

view Offline at https://defobasegroup.com/nsn/3302-01-343-2077
Body Length:
Between 1.080 inches and 1.135 inches
Body Width:
Between 1.080 inches and 1.135 inches
Body Height:
Between 0.070 inches and 0.140 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Burn in and bidirectional and monolithic and w/common clock
Inclosure Material:
Ceramic
Inclosure Configuration:
Pin grid array
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
45 input
Design Function And Quantity:
1 processor, pulse
Case Outline Source And Designator:
P-bc mil-m-38510
Current Rating Per Characteristic:
300.00 microamperes average forward current averaged over a full 60-hz cycle not applicable
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, digital, cmos, signal processor
Voltage Rating And Type Per Characteristic:
-0.3 volts power source and 7.0 volts power source
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
68 pin
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5962-01-345-2677

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0