NSN 5962-01-345-2682

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-345-2682

Overall Length:
1.280 inches
Overall Height:
0.400 inches
Body Length:
1.280 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
1260-01-165-3959 control-display
Features Provided:
W/enable and electrostatic sensitive and hermetically sealed and burn in
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
12 input
Case Outline Source And Designator:
D-9 mil-m-38510
Current Rating Per Characteristic:
150.00 milliamperes supply
150.00 milliamperes supply Terminal Surface Treatment:
Terminal Surface Treatment:
Terminal Surface Treatment: Solder
Terminal Surface Treatment: Solder Product Name:
Terminal Surface Treatment: Solder Product Name: Sram
Terminal Surface Treatment: Solder Product Name: Sram Voltage Rating And Type Per Characteristic:
Terminal Surface Treatment: Solder Product Name: Sram Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source
Terminal Surface Treatment: Solder Product Name: Sram Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Time Rating Per Chacteristic:

NSN 5962-01-345-2682

Memory Microcircuit - Page 2 of 2



Memory Capacity:

Unknown

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0