NSN 5962-01-345-5849

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-345-5849

Overall Length:
1.280 inches
Overall Height:
0.400 inches
Body Length:
1.280 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
650.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
1260-01-165-3959 control-display sys
Features Provided:
Erasable and 3-state output and asynchronous and w/disable and w/clock
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
22 input
Design Function And Quantity:
1 array, logic
Case Outline Source And Designator:
D-9 mil-m-38510
Current Rating Per Characteristic:
100.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
600 gate epid
Voltage Rating And Type Per Characteristic:
-2.0 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:

Err-060 and err-060

NSN 5962-01-345-5849

Memory Microcircuit - Page 2 of 2

A458a0



Time Rating Per Chacteristic:
55.00 nanoseconds access
Memory Device Type:
Programmable
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: