# NSN 5962-01-346-0072

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-346-0072

**Overall Length:** 1.280 inches **Overall Height:** 0.400 inches **Body Length:** 1.280 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 650.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **End Application:** 1260-01-165-3959 control-display sys **Features Provided:** Erasable and 3-state output and asynchronous and w/disable and w/clock **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 22 input **Case Outline Source And Designator:** D-9 mil-m-38510 **Current Rating Per Characteristic:** 100.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Product Name:** 600 gate epld Voltage Rating And Type Per Characteristic: -2.0 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 55.00 nanoseconds access Memory Device Type: Programmed

## NSN 5962-01-346-0072

Memory Microcircuit - Page 2 of 2



#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

### Unit Of Measure:

--

#### Demilitarization:

Yes - demil/mli

Fiig:

A458a0