NSN 5962-01-346-3370

Digital Microcircuit - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5962-01-346-3370

1.290 inches
Overall Height:
0.400 inches
Body Length:
1.290 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
200.0 milliwatts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
16 input
Design Function And Quantity:
1 control, bite summary
Case Outline Source And Designator:
D-3 mil-m-38510
Current Rating Per Characteristic:
35.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
Output correlator
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:
Err-060 and err-060
Time Rating Per Chacteristic:

25.00 nanoseconds delay

NSN 5962-01-346-3370

Digital Microcircuit - Page 2 of 2



Unpackaged Unit Weight:
6.5 grams
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:
-

Demilitarization:

Yes - demil/mli

Fiig:

A458a0