NSN 5962-01-346-5852

Memory Microcircuit - Page 1 of 2

Between 0.500 inches and 0.610 inches

Between 0.172 inches and 0.217 inches

Body Length: 1.490 inches Body Width:

Body Height:



View Online at https://aerobasegroup.com/nsn/5962-01-346-5852

Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Nha pn 113398-100 cage 19059 ei mrt printer
Features Provided:
Electrostatic sensitive and programmed and monolithic and ultraviolet erasable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
16 input
Criticality Code Justification:
Cbbl
Current Rating Per Characteristic:
100.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, 64-bit, prom, programmed
Voltage Rating And Type Per Characteristic:
7.0 volts total supply
Time Rating Per Chacteristic:
250.00 nanoseconds access
Memory Device Type:
Eprom
Special Features:
Make from eprom pn 8200504ya

Terminal Type And Quantity:

28 printed circuit

NSN 5962-01-346-5852

Memory Microcircuit - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0