NSN 5962-01-346-8836

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-346-8836 **Body Length:** 1.060 inches **Body Width:** 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and w/clock and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Octal 1 input **Design Function And Quantity:** 8 flip-flop **Case Outline Source And Designator:** D-8 mil-m-38510 **Current Rating Per Characteristic:** 100.00 milliamperes peak forward surge current horsepower metric **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 6.0 volts input **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 pin Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-346-8836

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0