NSN 5962-01-347-1694

Digital Microcircuit - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5962-01-347-1694

| 2.096 inches |
|--|
| Overall Height: |
| 0.425 inches |
| Body Length: |
| 2.096 inches |
| Body Width: |
| Between 0.510 inches and 0.620 inches |
| Body Height: |
| Between 0.155 inches and 0.210 inches |
| Maximum Power Dissipation Rating: |
| 1.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Asynchronous and monolithic and w/open collector and w/clock and w/reset |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| N-type metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 23 input |
| Design Function And Quantity: |
| 2 receiver and 2 transmitter |
| Case Outline Source And Designator: |
| D-5 mil-m-38510 |
| Current Rating Per Characteristic: |
| 175.00 milliamperes reverse current, dc absolute |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Dual asynchronous receiver/transmitter (duart) |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 6.0 volts power source |
| Capitance Rating Per Characteristic: |
| Err-060 |
| Test Data Document: |

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-347-1694

Digital Microcircuit - Page 2 of 2



| Ferminal Type A | and Q | uantity: |
|-----------------|-------|----------|
|-----------------|-------|----------|

40 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0