## NSN 5962-01-347-5529

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-347-5529

Overall Length:
0.840 inches
Overall Height:
0.400 inches
Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 decoder, one of four line
Case Outline Source And Designator:
D-2 mil-m-38510
Current Rating Per Characteristic:
5.50 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 6.0 volts power source
Time Rating Per Chacteristic:
7.80 nanoseconds propagation delay time, high to low level output and 7.80 nanoseconds propagation delay time, low to high level output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

16 printed circuit

**Terminal Type And Quantity:** 

## NSN 5962-01-347-5529

Digital Microcircuit - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A458a0