NSN 5962-01-347-5858

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-347-5858

Overall Height:
0.400 inches
Overall Width:
Between 0.290 inches and 0.320 inches
Body Length:
0.785 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Burn in and high speed and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 gate, nor
Case Outline Source And Designator:
Case Outline Source And Designator: D-1 mil-m-38510
D-1 mil-m-38510
D-1 mil-m-38510 Terminal Surface Treatment:
D-1 mil-m-38510 Terminal Surface Treatment: Solder
D-1 mil-m-38510 Terminal Surface Treatment: Solder Product Name:
D-1 mil-m-38510 Terminal Surface Treatment: Solder Product Name: Exclusive nor gate
D-1 mil-m-38510 Terminal Surface Treatment: Solder Product Name: Exclusive nor gate Voltage Rating And Type Per Characteristic:
D-1 mil-m-38510 Terminal Surface Treatment: Solder Product Name: Exclusive nor gate Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source
D-1 mil-m-38510 Terminal Surface Treatment: Solder Product Name: Exclusive nor gate Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document:
Terminal Surface Treatment: Solder Product Name: Exclusive nor gate Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

N/a

NSN 5962-01-347-5858

Digital Microcircuit - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0