

View Online at <https://aerobasegroup.com/nsn/5962-01-347-8622>

Body Length:

Between 0.442 inches and 0.460 inches

Body Width:

Between 0.442 inches and 0.460 inches

Body Height:

Between 0.060 inches and 0.100 inches

Maximum Power Dissipation Rating:

550.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Programmable and monolithic and w/disable

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

11 input

Case Outline Source And Designator:

C-4 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

One time programmable prom

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

35.00 nanoseconds access

Memory Device Type:

Prom

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0