## NSN 5962-01-348-0137

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-348-0137

view Offilite at https://defobasegroup.com/nsii/0302-01-040-0107
Body Length:
Between 0.342 inches and 0.358 inches
Body Width:
Between 0.342 inches and 0.358 inches
Body Height:
Between 0.060 inches and 0.100 inches
Maximum Power Dissipation Rating:
1.32 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and tested to mil-std-883 and burn in
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Input Circuit Pattern:
8 input
Design Function And Quantity:
4 comparator, voltage
Case Outline Source And Designator:
C-2 mil-m-38510
Current Rating Per Characteristic:
20.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
Precision voltage comparator
Voltage Rating And Type Per Characteristic:
33.0 volts power source
Time Rating Per Chacteristic:
200.00 nanoseconds response
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 leadless
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5962-01-348-0137

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0