

View Online at <https://aerobasegroup.com/nsn/5962-01-348-0399>

Overall Length:

Between 0.386 inches and 0.394 inches

Overall Height:

Between 0.053 inches and 0.069 inches

Overall Width:

Between 0.228 inches and 0.244 inches

Body Length:

Between 0.386 inches and 0.394 inches

Body Width:

Between 0.150 inches and 0.157 inches

Body Height:

Between 0.045 inches and 0.065 inches

Maximum Power Dissipation Rating:

75.0 milliwatts

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Bidirectional and schottky and low power and positive edge triggered and w/clock and parallel operation

Inclosure Material:

Plastic

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

1 shift register, universal

Current Rating Per Characteristic:

23.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

30.00 nanoseconds propagation delay time, high to low level output and 22.00 nanoseconds propagation delay time, low to high level output

Terminal Type And Quantity:

16 gullwing

Specification Data:

28480-1820-4267 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0