NSN 5962-01-348-7391

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-348-7391

view Offilite at https://defobasegroup.com/hist//0302-01-040-7331
Overall Length:
Between 0.790 inches and 0.800 inches
Overall Height:
0.320 inches
Overall Width:
Between 0.490 inches and 0.500 inches
Body Length:
Between 0.790 inches and 0.800 inches
Body Width:
Between 0.490 inches and 0.500 inches
Body Height:
0.145 inches
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Storage Tempurature Range:
-65.0 to 150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and high speed and hybrid and radiation hardened
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
4 input
Criticality Code Justification:
Feat
Design Function And Quantity:
1 detector
Current Rating Per Characteristic:
150.00 milliamperes supply
Terminal Surface Treatment:
Solder
Product Name:
Nuclear event detector
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
20.00 nanoseconds delay
Hybrid Technology Type:
Monolithic

Special Features:

Nuclear hardness critical item

NSN 5962-01-348-7391

Hybrid Microcircuit - Page 2 of 2

Fiig: A458a0



Nuclear Hardness Critical Feature:	
Hardened	
Test Data Document:	
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards,	etc.).
Terminal Type And Quantity:	
14 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	