NSN 5962-01-349-3394

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-349-3394

view Online at https://derobasegroup.com/nsn/0302-01-049-0094
Overall Length:
1.290 inches
Overall Height:
0.425 inches
Body Length:
1.290 inches
Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
Between 0.150 inches and 0.210 inches
Maximum Power Dissipation Rating:
1.04 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and 3-state output and programmed
Hermetically sealed and burn in and 3-state output and programmed Inclosure Material:
Inclosure Material:
Inclosure Material: Ceramic
Inclosure Material: Ceramic Inclosure Configuration:
Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line
Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form:
Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic
Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern:
Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 14 input
Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 14 input Case Outline Source And Designator:
Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 14 input Case Outline Source And Designator: D-3 mil-m-38510
Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 14 input Case Outline Source And Designator: D-3 mil-m-38510 Current Rating Per Characteristic: 190.00 milliamperes supply Terminal Surface Treatment:
Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 14 input Case Outline Source And Designator: D-3 mil-m-38510 Current Rating Per Characteristic: 190.00 milliamperes supply

-0.3 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

10.00 input picofarads and 13.00 output picofarads

Time Rating Per Chacteristic:

100.00 nanoseconds access

Memory Device Type:

Prom

Memory Capacity:

Unknown

NSN 5962-01-349-3394

Memory Microcircuit - Page 2 of 2



Test	Data	Doc	um	ent
------	------	-----	----	-----

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0