

View Online at <https://aerobasegroup.com/nsn/5962-01-349-4312>

Overall Length:

1.060 inches

Overall Height:

0.400 inches

Body Length:

1.060 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.130 inches and 0.185 inches

Maximum Power Dissipation Rating:

300.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

High impedance and w/disable and monolithic and bipolar and programmable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

10 input

Case Outline Source And Designator:

D-8 mil-m-38510

Current Rating Per Characteristic:

50.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

And-or invert gate array

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 12.0 volts power source

Time Rating Per Characteristic:

75.00 nanoseconds propagation delay time, high to low level output and 75.00 nanoseconds propagation delay time, low to high level output

Memory Device Type:

Pal

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0