## NSN 5962-01-349-5482

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-349-5482

Overall Height:
0.400 inches
Overall Width:
Between 0.290 inches and 0.320 inches
Body Length:
0.405 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
6625-01-242-2128
Features Provided:
Burn in and electrostatic sensitive and high speed and low noise
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
D-4 mil-m-38510
Current Rating Per Characteristic:
2.00 milliamperes forward current, nonrepetitive, peak total value absolute
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, linear, operational amplifier
Voltage Rating And Type Per Characteristic:
22.0 volts power source
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 printed circuit
Shelf Life:

N/a

## NSN 5962-01-349-5482

Linear Microcircuit - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A458a0