NSN 5962-01-349-5485

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-349-5485

Overall Length:
1.490 inches
Overall Height:
0.432 inches
Body Length:
1.490 inches
Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
Between 0.172 inches and 0.217 inches
Maximum Power Dissipation Rating:
1.4 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
6625-01-242-2128 test set, electronic systems
Features Provided:
Bipolar and monolithic and w/clock and asynchronous and w/strobe
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
18 input
Design Function And Quantity:
1 control
Case Outline Source And Designator:

D-10 mil-m-38510

Current Rating Per Characteristic:

250.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Vmebus controller (buscon)

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-349-5485

Digital Microcircuit - Page 2 of 2



Ferminal Type And Quai	ntity	:
------------------------	-------	---

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0