NSN 5962-01-349-5485

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-349-5485

| Overall Length: |
|------------------------------------------------------------------|
| 1.490 inches |
| Overall Height: |
| 0.432 inches |
| Body Length: |
| 1.490 inches |
| Body Width: |
| Between 0.500 inches and 0.610 inches |
| Body Height: |
| Between 0.172 inches and 0.217 inches |
| Maximum Power Dissipation Rating: |
| 1.4 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| 6625-01-242-2128 test set, electronic systems |
| Features Provided: |
| Bipolar and monolithic and w/clock and asynchronous and w/strobe |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 18 input |
| Design Function And Quantity: |
| 1 control |
| Case Outline Source And Designator: |

D-10 mil-m-38510

Current Rating Per Characteristic:

250.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Vmebus controller (buscon)

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-349-5485

Digital Microcircuit - Page 2 of 2



| Ferminal Type A | and Q | uantity: |
|-----------------|-------|----------|
|-----------------|-------|----------|

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0