NSN 5962-01-349-5493

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-349-5493

Overall Length:

Between 1.430 inches and 1.485 inches

Overall Height:

Between 0.280 inches and 0.400 inches

Body Length:

Between 1.430 inches and 1.485 inches

Body Width:

Between 0.245 inches and 0.310 inches

Body Height:

Between 0.140 inches and 0.175 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

6625-01-242-2128 test set, electronic systems

Features Provided:

W/clock and w/reset and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

15 input

Current Rating Per Characteristic:

150.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Capitance Rating Per Characteristic:

8.00 input picofarads and 12.00 output picofarads

Time Rating Per Chacteristic:

65.00 nanoseconds access

Memory Device Type:

First-in first-out

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-349-5493

Memory Microcircuit - Page 2 of 2



Ī	erminal	Type	And	Quant	tity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0