# NSN 5962-01-349-7583

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-349-7583

# **Overall Length:**

Between 0.670 inches and 0.710 inches

## **Overall Height:**

Between 0.186 inches and 0.410 inches

# **Body Length:**

Between 0.670 inches and 0.710 inches

#### **Body Width:**

0.300 inches

#### **Body Height:**

Between 0.005 inches and 0.161 inches

# **Maximum Power Dissipation Rating:**

1.0 watts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

High performance and monolithic and wideband and high precision and high speed and hermetically sealed and fast settling

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

Quad 2 input

### **Design Function And Quantity:**

4 amplifier, operational, general purpose

### **Current Rating Per Characteristic:**

11.00 milliamperes reverse current, dc absolute

### **Terminal Surface Treatment:**

Solder

Product Name:

Operational amplifier array

### Voltage Rating And Type Per Characteristic:

-18.0 volts power source and 18.0 volts power source

### **Time Rating Per Chacteristic:**

1.50 milliseconds agc threshold nanoamperes

## Terminal Type And Quantity:

14 printed circuit

#### **Specification Data:**

97384-50301-90017 manufacturers specification control

# Shelf Life:

N/a

# NSN 5962-01-349-7583

Linear Microcircuit - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

