NSN 5962-01-349-7583

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-349-7583

Overal	I Length:

Between 0.670 inches and 0.710 inches

Overall Height:

Between 0.186 inches and 0.410 inches

Body Length:

Between 0.670 inches and 0.710 inches

Body Width:

0.300 inches

Body Height:

Between 0.005 inches and 0.161 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

High performance and monolithic and wideband and high precision and high speed and hermetically sealed and fast settling

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

Quad 2 input

Design Function And Quantity:

4 amplifier, operational, general purpose

Current Rating Per Characteristic:

11.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Operational amplifier array

Voltage Rating And Type Per Characteristic:

-18.0 volts power source and 18.0 volts power source

Time Rating Per Chacteristic:

1.50 milliseconds agc threshold nanoamperes

Terminal Type And Quantity:

14 printed circuit

Specification Data:

97384-50301-90017 manufacturers specification control

Shelf Life:

N/a

NSN 5962-01-349-7583

Linear Microcircuit - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0