## NSN 5962-01-350-3933

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-350-3933
Overall Length:
1.060 inches
Overall Height:
0.400 inches
Body Length:
1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.130 inches and 0.185 inches
Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and programmed and bipolar and electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
14 input
Case Outline Source And Designator:
D-8 mil-m-38510
Current Rating Per Characteristic:
105.00 milliamperes supply
Terminal Surface Treatment:
Solder
Product Name:
Registered and-or gate array
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
30.00 nanoseconds propagation delay
Memory Device Type:
Pal
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## NSN 5962-01-350-3933

Memory Microcircuit - Page 2 of 2



## Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0